

AKG

Description

The AKG gooseneck models in the Discreet Acoustics Modular series provide length and mounting options for permanent and semi-permanent installations. The flexible goosenecks allow for silent positioning of the microphone while the thin profile and matte gray finish make them inconspicuous in use. All models require phantom power enables the operating engineer to check system status at a distance. A bass roll-off beginning at 250 HZ is provided for control of proximity effect and low frequency structural vibration of proximity effect and low frequency structural vibrations. Control of the light ring and bass roll-off is handled by internal jumpers.

The AKG gooseneck mounting modules is available in the size is 30cm. These size is in distinct product group are available:

Basic series: The products are designed to be mounted permanently on a surface and require a 0.236 inch mounting hole. A slotted bolt and rubber bushings are included with each unit. The rubber bushings minimize structure-borne vibrations and the slotted bolt allows the cable and mini-XLR connector to pass through the mounting hole. Phantom power conditioning is provided by the Discreet Power Adapter (DPA) which attaches to the cable and is terminated in a standard 3-pin XLR male connector.

Specifications

Powering: 9-52Vdc, requires DPA adapter

Connector: 3-pin XLR

Cable length: 80 inches

Finish: dark gray matte

Included accessories: B 18 Battery supply

H 500 shock mount

Features

1. Accomodation of 5different capsule models
2. Integrated switchable LED indicator bass roll-off
3. Integrated bass roll-off
4. Rugged design
- 5.

Non-reflective gray color

Limited Warranty

AKG acoustics warrants AKG products against in material or workmanship for a period of two years from the date of original purchase for use, and agrees to repair or, at our option, replace any defective unit without charge for either parts or labor.